

Silikon-Spray (Silicone-Spray)



[EG-Sicherheitsblatt](#)

Universal lubricant, separating agent, greasing agent, protection and impregnating agent for the industrial sector, hobbies, trades, automotive, sports etc.

Silikon-Spray (Silicone-Spray)

- Combination of various high-quality silicones
- Prohibits oxidation and corrosion on metal parts
- Protects rubber parts from drying out
- Care product for plastic surfaces
- Protects against freezing
- Penetrating oil for difficult to reach areas
- Water-repellent
- Contains environmentally friendly propellant gas

Instructions for use:

Part must be grease-free, clean and dry to ensure the spray adheres better. Shake well before use. Hold the spray button in arrow direction, upright at a distance of approx. 25 – 30 cm from the part. The thickness of the silicone film can be regulated by the spray duration, however, it should only be sprayed for a short time. The greater the distance, the finer and more even the silicone film will be.

Packaging

Silikon-Spray (Silicone-Spray) is available in 400 ml aerosol cans.

Safety

The container is pressurized. Protect from sun and temperatures above 50° C. Do not open forcibly or burn, even when empty. Do not inhale the aerosol. Do not allow the contents to enter the waste water system. Do not spray people. Keep away from naked flames and incandescent materials. Keep away from sources of combustion – do not smoke -. Keep away from children. Only use in well-ventilated areas. In the case of contact with eyes, keep the eye open and rinse with lots of water. Contact an eye specialist if the irritation does not subside.

Disposal advice

Do not dispose of the can in the domestic waste. Discard the totally emptied can into the recyclable waste container (green dot)