Printing date 09.02.2016 Version number 1 Revision: 09.02.2016

SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier

· Trade name: Edelstahl-Spray

· Article number: -

· 1.2 Relevant identified uses of the substance or mixture and uses advised against

· Sector of Use

SU21 Consumer uses: Private households / general public / consumers

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

· Application of the substance / the mixture Coating material

· 1.3 Details of the supplier of the safety data sheet

· Manufacturer/Supplier:

Klostermann Chemie GmbH & Co. KG von-dem-Bussche-Münch-Str. 4 32339 Espelkamp

Tel.: 05772/6711 Fax: 05772/6799

www.klostermann-chemie.de

E-Mail: info@klostermann-chemie.de

- · Further information obtainable from: Product safety department
- · 1.4 Emergency telephone number:

Poison Control Center Mainz - 24 hour emergency service - phone: +49 (0) 6131/19240

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.



Eye Irrit. 2 H319 Causes serious eye irritation.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

· 2.2 Label elements

· Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms





GHS02

GHS07

- · Signal word Danger
- · Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

H319 Causes serious eye irritation.

H412 Harmful to aquatic life with long lasting effects.

· Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

(Contd. on page 2)

Printing date 09.02.2016 Version number 1 Revision: 09.02.2016

Trade name: Edelstahl-Spray

(Contd. of page 1)

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P251 Do not pierce or burn, even after use.

P211 Do not spray on an open flame or other ignition source.

P271 Use only outdoors or in a well-ventilated area.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

· Additional information:

EUH066 Repeated exposure may cause skin dryness or cracking.

Contains N-(3-(trimethoxysilyl)propyl)ethylenediamine, nickel powder (particle diameter <math>< 1 mm). May produce an allergic reaction.

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

- · 3.2 Chemical characterisation: Mixtures
- · Description: Mixture of substances listed below with nonhazardous additions.

| · Dangerous components: | | |
|--|--|---------|
| CAS: 74-98-6 EINECS: 200-827-9 Reg.nr.: 01-2119486944-21-xxxx | propane Flam. Gas 1, H220; Press. Gas C, H280 | 10-25% |
| CAS: 106-97-8 EINECS: 203-448-7 Reg.nr.: 01-2119474691-32-xxxx | butane Flam. Gas 1, H220; Press. Gas C, H280 | 10-25% |
| CAS: 75-28-5 EINECS: 200-857-2 Reg.nr.: 01-2119485395-27-xxxx | isobutane Flam. Gas 1, H220; Press. Gas C, H280 | 10-25% |
| CAS: 67-64-1 EINECS: 200-662-2 Reg.nr.: 01-2119471330-49 | acetone Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H336 | 10-25% |
| CAS: 141-78-6 EINECS: 205-500-4 Reg.nr.: 01-2119475103-46-xxxx | ethyl acetate Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H336 | 2.5-10% |
| CAS: 1330-20-7 EINECS: 215-535-7 Reg.nr.: 01-2119486136-34 | xylene Flam. Liq. 3, H226; Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315 | 2.5-10% |
| CAS: 64742-95-6 918-668-5 Reg.nr.: 01-2119455851-35-xxxx | Solvent naphtha (petroleum), light arom. Flam. Liq. 3, H226; Asp. Tox. 1, H304; Aquatic Chronic 2, H411; STOT SE 3, H335-H336 | 2.5-10% |
| CAS: 1314-13-2 EINECS: 215-222-5 | zinc oxide �� Aquatic Acute 1, H400; Aquatic Chronic 1, H410 | < 1% |
| CAS: 7440-02-0 EINECS: 231-111-4 | nickel powder (particle diameter < 1 mm) Carc. 2, H351; STOT RE 1, H372; Skin Sens. 1, H317; Aquatic Chronic 3, H412 | < 1% |

(Contd. on page 3)

Printing date 09.02.2016 Version number 1 Revision: 09.02.2016

Trade name: Edelstahl-Spray

| (Cont | d. of page 2) |
|---|---------------|
| N-(3-(trimethoxysilyl)propyl)ethylenediamine | < 1% |
| Eye Dam. 1, H318; | |
| naphthalene Carc. 2, H351; Aquatic Acute 1, H400; Aquatic Chronic 1, H410; Acute Tox. 4, H302 | < 1% |

[·] Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · General information: Immediately remove any clothing soiled by the product.
- · After inhalation:

Supply fresh air.

Seek medical treatment in case of complaints.

· After skin contact:

Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

· After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

· After swallowing:

Rinse out mouth and then drink plenty of water.

If symptoms persist consult doctor.

- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- · 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · 5.2 Special hazards arising from the substance or mixture Can form explosive gas-air mixtures.
- · 5.3 Advice for firefighters
- · Protective equipment: Wear self-contained respiratory protective device.
- · Additional information Cool endangered receptacles with water spray.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

- 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- 6.3 Methods and material for containment and cleaning up: Ensure adequate ventilation.
- · 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling Use only in well ventilated areas.

(Contd. on page 4)

Printing date 09.02.2016 Version number 1 Revision: 09.02.2016

Trade name: Edelstahl-Spray

· Information about fire - and explosion protection:

(Contd. of page 3)



Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Do not spray onto a naked flame or any incandescent material.

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50 °C, i.e. electric lights. Do not pierce or burn, even after use.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles:

Store in a cool location.

Observe official regulations on storing packagings with pressurised containers.

- · Information about storage in one common storage facility: Store away from oxidising agents.
- · Further information about storage conditions: None.
- · 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- · Additional information about design of technical facilities: No further data; see item 7.
- · 8.1 Control parameters

| T | . 1::41 414 | | g at the workplace: |
|--------------------|-------------------|------------------|---------------------|
| · Ingreatents with | . umu vaiues inai | reauire monuorin | g at the workblace: |
| | | | |

106-97-8 butane

WEL Short-term value: 1810 mg/m³, 750 ppm Long-term value: 1450 mg/m³, 600 ppm Carc (if more than 0.1% of buta-1.3-diene)

67-64-1 acetone

WEL Short-term value: 3620 mg/m³, 1500 ppm Long-term value: 1210 mg/m³, 500 ppm

141-78-6 ethyl acetate

WEL Short-term value: 400 ppm Long-term value: 200 ppm

1330-20-7 xylene

WEL Short-term value: 441 mg/m³, 100 ppm Long-term value: 220 mg/m³, 50 ppm Sk; BMGV

7440-02-0 nickel powder (particle diameter < 1 mm)

WEL Long-term value: 0.5 mg/m³ as Ni; Sk; Carc

· Ingredients with biological limit values:

1330-20-7 xylene

BMGV 650 mmol/mol creatinine

Medium: urine

Sampling time: post shift Parameter: methyl hippuric acid

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed. Wash hands before breaks and at the end of work.

(Contd. on page 5)

Printing date 09.02.2016 Version number 1 Revision: 09.02.2016

Trade name: Edelstahl-Spray

(Contd. of page 4)

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes and skin.

· Respiratory protection:

Use suitable respiratory protective device in case of insufficient ventilation.

Short term filter device:

Filter A/P2

· Protection of hands:



Protective gloves

· Material of gloves

Nitrile rubber, NBR

Recommended thickness of the material: ≥ 0.4 mm

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

· Body protection: Protective work clothing

SECTION 9: Physical and chemical properties

| | 9 | 1 Information | on basic | nhysical | and chemic | al properties |
|---|-----|---------------|----------|------------|------------|---------------|
| - | 7.1 | i injoimunon | on vasic | Dii vsicui | ини спети | ui bibbeines |

· General Information

· Appearance:

Form: Aerosol

Colour: According to product specification

Odour: CharacteristicOdour threshold: Not determined.

· pH-value: Not determined.

· Change in condition

Melting point/Melting range: Undetermined.

Boiling point/Boiling range: Not applicable, as aerosol.

· Flash point: Not applicable, as aerosol.

· Flammability (solid, gaseous): Not applicable.

· Ignition temperature: 365 °C

· Decomposition temperature: Not determined.

· Self-igniting: Product is not selfigniting.

· Danger of explosion: Not determined.

· Explosion limits:

Lower: 1.5 Vol %
Upper: 13.0 Vol %
• Oxidising properties Not determined.

· Vapour pressure at 20 °C: 4200 hPa

• **Density at 20 °C:** 0.718 g/cm³

· Relative density Not determined.

(Contd. on page 6)

Printing date 09.02.2016 Version number 1 Revision: 09.02.2016

Trade name: Edelstahl-Spray

(Contd. of page 5)

Vapour densityEvaporation rateNot determined.Not applicable.

· Solubility in / Miscibility with

water: Not miscible or difficult to mix.

· Partition coefficient (n-octanol/water): Not determined.

· Viscosity:

 Dynamic:
 Not determined.

 Kinematic:
 Not determined.

 VOC (EC) %
 84.48 %

 VOCV (CH)
 84.48 %

• 9.2 Other information No further relevant information available.

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.

| · LD/LC5 | · LD/LC50 values relevant for classification: | | |
|----------|---|---------------------|--|
| | 1330-20-7 xylene | | |
| Oral | LD50 | 4300 mg/kg (rat) | |
| Dermal | LD50 | 2000 mg/kg (rabbit) | |
| 64742-9 | 64742-95-6 Solvent naphtha (petroleum), light arom. | | |
| Oral | LD50 | >6800 mg/kg (rat) | |
| Dermal | LD50 | >3400 mg/kg (rab) | |
| 1314-13 | 1314-13-2 zinc oxide | | |
| Oral | LD50 | > 5000 mg/kg (rat) | |

- · Primary irritant effect:
- · Skin corrosion/irritation Based on available data, the classification criteria are not met.
- · Serious eye damage/irritation

Causes serious eye irritation.

- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure Based on available data, the classification criteria are not met.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

Printing date 09.02.2016 Version number 1 Revision: 09.02.2016

Trade name: Edelstahl-Spray

(Contd. of page 6)

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · Ecotoxical effects:
- · Remark: Harmful to fish
- $\cdot \textit{Additional ecological information:}$
- · General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

Harmful to aquatic organisms

- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods:

Containers can be recycled if completely empty; if not, dispose product/containers as dangerous waste. Observe local regulations.

· Recommendation

Completely emptied packagings can be given for recycling. (In accordance with local authority regulations, take to chemical/physical treatment plant.)

| · European | waste | catal | logue |
|------------|-------|-------|-------|
|------------|-------|-------|-------|

15 01 04 metallic packaging

16 05 05 gases in pressure containers other than those mentioned in 16 05 04

SECTION 14: Transport information

- · 14.1 UN-Number
- · ADR, IMDG, IATA UN1950

· 14.2 UN proper shipping name

ADR UN1950 AEROSOLS

· IMDG AEROSOLS

· IATA AEROSOLS, flammable

- · 14.3 Transport hazard class(es)
- $\cdot ADR$



· Class 2 5F Gases.

(Contd. on page 8)

Printing date 09.02.2016 Version number 1 Revision: 09.02.2016

Trade name: Edelstahl-Spray

| | (Contd. of page |
|---------------------------------------|------------------------------------|
| Label | 2.1 |
| IMDG, IATA | |
| 2 | |
| Class | 2.1 |
| Label | 2.1 |
| 14.4 Packing group | |
| ADR, IMDG, IATA | Void |
| 14.5 Environmental hazards: | |
| Marine pollutant: | No |
| 14.6 Special precautions for user | Warning: Gases. |
| Danger code (Kemler): | - |
| EMS Number: | F-D,S-U |
| 14.7 Transport in bulk according to A | |
| Marpol and the IBC Code | Not applicable. |
| Transport/Additional information: | |
| ADR | |
| Limited quantities (LQ) | 1L |
| Excepted quantities (EQ) | Code: E0 |
| | Not permitted as Excepted Quantity |
| Transport category | 3 |
| Tunnel restriction code | E |
| IMDG | |
| Limited quantities (LQ) | IL |
| Excepted quantities (EQ) | Code: E0 |
| | Not permitted as Excepted Quantity |
| UN "Model Regulation": | UN 1950 AEROSOLS, 2.1 |

SECTION 15: Regulatory information

- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P3a FLAMMABLE AEROSOLS
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.
- $\cdot \textit{Exposure scenario}(s)$

Exposure scenario(s) of ingredients (if present) are available on request at:

info@klostermann-chemie.de

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H220 Extremely flammable gas.

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H280 Contains gas under pressure; may explode if heated.

(Contd. on page 9)

Printing date 09.02.2016 Version number 1 Revision: 09.02.2016

Trade name: Edelstahl-Spray

(Contd. of page 8)

H302 Harmful if swallowed.

H304 May be fatal if swallowed and enters airways.

H312 Harmful in contact with skin.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

H351 Suspected of causing cancer.

H372 Causes damage to organs through prolonged or repeated exposure.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

H411 Toxic to aquatic life with long lasting effects.

H412 Harmful to aquatic life with long lasting effects.

· Department issuing SDS: Product safety department

· Contact: Head of Product Safety Department

· Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International

Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOCV: Lenkungsabgabe auf flüchtigen organischen Verbindungen, Schweis (Swiss Ordinance on volatile organic compounds)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Gas 1: Flammable gases, Hazard Category 1

Aerosol 1: Flammable aerosols, Hazard Category 1 Press. Gas C: Gases under pressure: Compressed gas

Flam. Liq. 2: Flammable liquids, Hazard Category 2

Flam. Liq. 3: Flammable liquids, Hazard Category 3

Acute Tox. 4: Acute toxicity, Hazard Category 4

Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2

Eye Dam. 1: Serious eye damage/eye irritation, Hazard Category 1

Eye Irrit. 2: Serious eye damage/eye irritation, Hazard Category 2

Skin Sens. 1: Sensitisation - Skin, Hazard Category 1

 $Carc.\ 2:\ Carcinogenicity,\ Hazard\ Category\ 2$

STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3

STOT RE 1: Specific target organ toxicity - Repeated exposure, Hazard Category 1

Asp. Tox. 1: Aspiration hazard, Hazard Category 1

 $Aquatic\ Acute\ 1:\ Hazardous\ to\ the\ aquatic\ environment\ -\ Acute Hazard,\ Category\ 1$

Aquatic Chronic 1: Hazardous to the aquatic environment - Chronic Hazard, Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - Chronic Hazard, Category 2

Aquatic Chronic 3: Hazardous to the aquatic environment - Chronic Hazard, Category 3