

Zinc-Spray 700 Klostermann Chemie

Version number: GHS 2.1
Replaces version of: 19.04.2021 (GHS 1)

Revision: 25.11.2021

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name	Zinc-Spray 700 Klostermann Chemie
Unique formula identifier (UFI)	2A20-U0DS-100W-PM43
Article number	583

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses	Paint, coating and lacquer Industrial uses Professional uses Consumer uses
--------------------------	---

1.3 Details of the supplier of the safety data sheet

Klostermann Chemie GmbH & Co.KG
Von-dem-Bussche-Münch-Straße 4
32339 Espelkamp
Germany

Telephone: +49 (0) 5772 6711
e-mail: info@klostermann-chemie.de
Website: www.klostermann-chemie.de

e-mail (competent person) info@klostermann-chemie.de (Tim Schürstedt)

1.4 Emergency telephone number

Poison centre		
Name	Postal code/city	Telephone
Beratungsstelle bei Vergiftungen Giftinformationszentrale der Länder Rheinland-Pfalz und Hessen	55131 Mainz	+49 (0) 6131-19240

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 (CLP)

Section	Hazard class	Category	Hazard class and category	Hazard statement
2.3	aerosols	1	Aerosol 1	H222,H229
3.2	skin corrosion/irritation	2	Skin Irrit. 2	H315
4.1A	hazardous to the aquatic environment - acute hazard	1	Aquatic Acute 1	H400
4.1C	hazardous to the aquatic environment - chronic hazard	1	Aquatic Chronic 1	H410

For full text of abbreviations: see SECTION 16.

The most important adverse physicochemical, human health and environmental effects
Spillage and fire water can cause pollution of watercourses.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008 (CLP)

- Signal word danger

Zinc-Spray 700 Klostermann Chemie

Version number: GHS 2.1
Replaces version of: 19.04.2021 (GHS 1)

Revision: 25.11.2021

- Pictograms

GHS02, GHS07, GHS09



- Hazard statements

H222 Extremely flammable aerosol.
H229 Pressurised container: May burst if heated.
H315 Causes skin irritation.
H410 Very toxic to aquatic life with long lasting effects.

- Precautionary statements

P101 If medical advice is needed, have product container or label at hand.
P102 Keep out of reach of children.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211 Do not spray on an open flame or other ignition source.
P251 Do not pierce or burn, even after use.
P273 Avoid release to the environment.
P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection/....
P391 Collect spillage.
P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

- Hazardous ingredients for labelling

Polymeric reaction products of fatty acids and ethoxylated alcohols with diethylenetriamine and 2,5-furandione

2.3 Other hazards

of no significance

SECTION 3: Composition/information on ingredients

3.1 Substances

Not relevant (mixture)

3.2 Mixtures

Description of the mixture

Name of substance	Identifier	Wt%	Classification acc. to GHS	Pictograms
Butane	CAS No 106-97-8 EC No 203-448-7 REACH Reg. No 01-2119474691-32- xxxx	25 – < 50	Flam. Gas 1A / H220 Press. Gas L / H280	
Zinc powder - zinc dust (stabilized)	CAS No 7440-66-6	25 – < 50	Aquatic Acute 1 / H400 Aquatic Chronic 1 / H410	
Propane	CAS No 74-98-6 EC No 200-827-9 REACH Reg. No 01-2119486944-21- xxxx	10 – < 25	Flam. Gas 1A / H220 Press. Gas L / H280	

Zinc-Spray 700 Klostermann Chemie

Version number: GHS 2.1
Replaces version of: 19.04.2021 (GHS 1)

Revision: 25.11.2021

Name of substance	Identifier	Wt%	Classification acc. to GHS	Pictograms
Xylene	CAS No 1330-20-7 EC No 215-535-7 Index No 601-022-00-9 REACH Reg. No 01-2119488216-32- xxxx	1 - < 5	Flam. Liq. 3 / H226 Acute Tox. 4 / H312 Acute Tox. 4 / H332 Skin Irrit. 2 / H315 Asp. Tox. 1 / H304	
Ethylbenzene	CAS No 100-41-4 EC No 202-849-4 REACH Reg. No 01-2119489370-35- xxxx	1 - < 5	Flam. Liq. 2 / H225 Acute Tox. 4 / H332 STOT RE 2 / H373 Asp. Tox. 1 / H304 Aquatic Chronic 3 / H412	
Acetone	CAS No 67-64-1 EC No 200-662-2 REACH Reg. No 01-2119471330-49- xxxx 01-2119498062-37- xxxx	1 - < 5	Flam. Liq. 2 / H225 Eye Irrit. 2 / H319 STOT SE 3 / H336	
Zinc oxide	CAS No 1314-13-2 EC No 215-222-5 Index No 030-013-00-7 REACH Reg. No 01-2119463881-32- xxxx	1 - < 5	Aquatic Acute 1 / H400 Aquatic Chronic 1 / H410	
Hydrocarbons, C9, aromatics	CAS No 64742-95-6 EC No 918-668-5 Index No 649-356-00-4 REACH Reg. No 01-2119455851-35- xxxx	1 - < 5	Flam. Liq. 3 / H226 STOT SE 3 / H335 STOT SE 3 / H336 Asp. Tox. 1 / H304 Aquatic Chronic 2 / H411	
Polymeric reaction products of fatty acids and ethoxylated alcohols with diethylenetriamine and 2,5-furandione	CAS No 1268617-32-8	< 1	Skin Sens. 1 / H317 Aquatic Acute 1 / H400 Aquatic Chronic 1 / H410	
Fatty acids, tall-oil, reaction products with diethylenetriamine	CAS No 61790-69-0 EC No 263-160-2 REACH Reg. No 01-2119411392-51- xxxx	< 1	Acute Tox. 4 / H302 Skin Corr. 1 / H314 STOT RE 2 / H373 Aquatic Acute 1 / H400 Aquatic Chronic 1 / H410	

Zinc-Spray 700 Klostermann Chemie

Version number: GHS 2.1
Replaces version of: 19.04.2021 (GHS 1)

Revision: 25.11.2021

Name of substance	Specific Conc. Limits	M-Factors	ATE	Exposure route
Xylene	-	-	1,100 mg/kg 11 mg/l/4h	dermal inhalation: vapour
Ethylbenzene	-	-	11 mg/l/4h	inhalation: vapour
Fatty acids, tall-oil, reaction products with diethylenetriamine	-	-	500 mg/kg	oral

For full text of abbreviations: see SECTION 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General notes

Do not leave affected person unattended. Remove victim out of the danger area. Keep affected person warm, still and covered. Take off immediately all contaminated clothing. In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness place person in the recovery position. Never give anything by mouth.

Following inhalation

If breathing is irregular or stopped, immediately seek medical assistance and start first aid actions. In case of respiratory tract irritation, consult a physician. Provide fresh air.

Following skin contact

Wash with plenty of soap and water.

Following eye contact

Remove contact lenses, if present and easy to do. Continue rinsing. Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart.

Following ingestion

Rinse mouth with water (only if the person is conscious). Do NOT induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms and effects are not known to date.

4.3 Indication of any immediate medical attention and special treatment needed

none

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Water spray, BC-powder

Unsuitable extinguishing media

Water jet

5.2 Special hazards arising from the substance or mixture

Hazardous combustion products

Carbon monoxide (CO), Carbon dioxide (CO₂)

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Co-ordinate firefighting measures to the fire surroundings. Do not allow firefighting water to enter drains or water courses. Collect contaminated firefighting water separately. Fight fire with normal precautions from a reasonable distance.

Zinc-Spray 700 Klostermann Chemie

Version number: GHS 2.1
Replaces version of: 19.04.2021 (GHS 1)

Revision: 25.11.2021

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Remove persons to safety.

For emergency responders

Wear breathing apparatus if exposed to vapours/dust/spray/gases.

6.2 Environmental precautions

Keep away from drains, surface and ground water. Retain contaminated washing water and dispose of it. If substance has entered a water course or sewer, inform the responsible authority.

6.3 Methods and material for containment and cleaning up

Advice on how to contain a spill

Covering of drains

Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.

6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Recommendations

- Measures to prevent fire as well as aerosol and dust generation

Use local and general ventilation. Use only in well-ventilated areas.

Advice on general occupational hygiene

Wash hands after use. Do not eat, drink and smoke in work areas. Remove contaminated clothing and protective equipment before entering eating areas. Never keep food or drink in the vicinity of chemicals. Never place chemicals in containers that are normally used for food or drink. Keep away from food, drink and animal feedingstuffs.

7.2 Conditions for safe storage, including any incompatibilities

Managing of associated risks

- Flammability hazards

Do not spray on an open flame or other ignition source. Protect from sunlight.

- Packaging compatibilities

Keep only in original container.

7.3 Specific end use(s)

See section 16 for a general overview.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Zinc-Spray 700 Klostermann Chemie

Version number: GHS 2.1
Replaces version of: 19.04.2021 (GHS 1)

Revision: 25.11.2021

Occupational exposure limit values (Workplace Exposure Limits)

Country	Name of agent	CAS No	Identifier	TWA [ppm]	TWA [mg/m ³]	STEL [ppm]	STEL [mg/m ³]	Ceiling-C [ppm]	Ceiling-C [mg/m ³]	Notation	Source
DE	hydrocarbon mixture (RCP method)		AGW		150		300				TRGS 900
DE	ethylbenzene	100-41-4	MAK	20	88	40	176				DFG
DE	ethylbenzene	100-41-4	AGW	20	88	40	176			H, Y	TRGS 900
DE	butane	106-97-8	AGW	1,000	2,400	4,000	9,600				TRGS 900
DE	n-butane	106-97-8	MAK	1,000	2,400	4,000	9,600				DFG
DE	zinc, inorganic compounds	1314-13-2	MAK		0.1		0.4			r	DFG
DE	zinc, inorganic compounds	1314-13-2	MAK		2		4			i	DFG
DE	xylene, mixture of isomers	1330-20-7	MAK	50	220	100	440				DFG
DE	xylene, mixture of isomers	1330-20-7	AGW	50	220	100	440			H	TRGS 900
DE	acetone	67-64-1	MAK	500	1,200	1,000	2,400				DFG
DE	acetone	67-64-1	AGW	500	1,200	1,000	2,400			Y	TRGS 900
DE	propane	74-98-6	AGW	1,000	1,800	4,000	7,200				TRGS 900
DE	propane	74-98-6	MAK	1,000	1,800	4,000	7,200				DFG
DE	zinc	7440-66-6	MAK		0.1		0.4			r	DFG
DE	zinc	7440-66-6	MAK		2		4			i	DFG
EU	ethylbenzene	100-41-4	IOELV	100	442	200	884				2000/39/EC
EU	xylene	1330-20-7	IOELV	50	221	100	442				2000/39/EC
EU	acetone	67-64-1	IOELV	500	1,210						2000/39/EC

Notation

Ceiling-C

ceiling value is a limit value above which exposure should not occur

H

absorbed through the skin

i

inhalable fraction

r

respirable fraction

STEL

short-term exposure limit: a limit value above which exposure should not occur and which is related to a 15-minute period (unless otherwise specified)

TWA

time-weighted average (long-term exposure limit); measured or calculated in relation to a reference period of 8 hours

Y

time-weighted average (unless otherwise specified)
a risk of developmental toxicity does not need to be expected if the occupational exposure limit value and the biological limit value (BGW) are adhered to

Biological limit values

Country	Name of agent	Parameter	Notation	Identifier	Value	Source
DE	ethylbenzene	mandelic acid, benzoylformic acid		BAT	250 mg/l	DFG
DE	ethylbenzene	mandelic acid, benzoylformic acid	crea	BLV	250 mg/g	TRGS 903

Zinc-Spray 700 Klostermann Chemie

Version number: GHS 2.1
Replaces version of: 19.04.2021 (GHS 1)

Revision: 25.11.2021

Biological limit values						
Country	Name of agent	Parameter	Notation	Identifier	Value	Source
DE	xylene, mixture of isomers	methylhippuric acids		BAT	2,000 mg/l	DFG
DE	xylene, mixture of isomers	methylhippuric acids		BLV	2,000 mg/l	TRGS 903
DE	Aceton	Aceton		BAT	50 mg/l	DFG
DE	Aceton	Aceton		BAT (BAR)	2.5 mg/l	DFG
DE	acetone	acetone		BLV	80 mg/l	TRGS 903

Notation

crea creatinine

Relevant DNELs of components of the mixture						
Name of substance	CAS No	Endpoint	Threshold level	Protection goal, route of exposure	Used in	Exposure time
Xylene	1330-20-7	DNEL	221 mg/m ³	human, inhalatory	worker (industry)	chronic - systemic effects
Xylene	1330-20-7	DNEL	442 mg/m ³	human, inhalatory	worker (industry)	acute - systemic effects
Xylene	1330-20-7	DNEL	221 mg/m ³	human, inhalatory	worker (industry)	chronic - local effects
Xylene	1330-20-7	DNEL	442 mg/m ³	human, inhalatory	worker (industry)	acute - local effects
Xylene	1330-20-7	DNEL	212 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects
Ethylbenzene	100-41-4	DNEL	77 mg/m ³	human, inhalatory	worker (industry)	chronic - systemic effects
Ethylbenzene	100-41-4	DNEL	293 mg/m ³	human, inhalatory	worker (industry)	acute - local effects
Ethylbenzene	100-41-4	DNEL	180 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects
Acetone	67-64-1	DNEL	1,210 mg/m ³	human, inhalatory	worker (industry)	chronic - systemic effects
Acetone	67-64-1	DNEL	2,420 mg/m ³	human, inhalatory	worker (industry)	acute - local effects
Acetone	67-64-1	DNEL	186 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects
Hydrocarbons, C9, aromatics	64742-95-6	DNEL	150 mg/m ³	human, inhalatory	worker (industry)	chronic - systemic effects
Hydrocarbons, C9, aromatics	64742-95-6	DNEL	25 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects

Relevant PNECs of components of the mixture						
Name of substance	CAS No	Endpoint	Threshold level	Organism	Environmental compartment	Exposure time
Xylene	1330-20-7	PNEC	0.327 mg/l	aquatic organisms	freshwater	short-term (single instance)
Xylene	1330-20-7	PNEC	0.327 mg/l	aquatic organisms	marine water	short-term (single instance)
Xylene	1330-20-7	PNEC	6.58 mg/l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)

Zinc-Spray 700 Klostermann Chemie

Version number: GHS 2.1
Replaces version of: 19.04.2021 (GHS 1)

Revision: 25.11.2021

Relevant PNECs of components of the mixture						
Name of substance	CAS No	Endpoint	Threshold level	Organism	Environmental compartment	Exposure time
Xylene	1330-20-7	PNEC	12.46 mg/kg	aquatic organisms	freshwater sediment	short-term (single instance)
Xylene	1330-20-7	PNEC	12.46 mg/kg	aquatic organisms	marine sediment	short-term (single instance)
Xylene	1330-20-7	PNEC	2.31 mg/kg	terrestrial organisms	soil	short-term (single instance)
Ethylbenzene	100-41-4	PNEC	0.1 mg/l	aquatic organisms	freshwater	short-term (single instance)
Ethylbenzene	100-41-4	PNEC	0.01 mg/l	aquatic organisms	marine water	short-term (single instance)
Ethylbenzene	100-41-4	PNEC	9.6 mg/l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
Ethylbenzene	100-41-4	PNEC	13.7 mg/kg	aquatic organisms	freshwater sediment	short-term (single instance)
Ethylbenzene	100-41-4	PNEC	1.37 mg/kg	aquatic organisms	marine sediment	short-term (single instance)
Ethylbenzene	100-41-4	PNEC	2.68 mg/kg	terrestrial organisms	soil	short-term (single instance)
Zinc oxide	1314-13-2	PNEC	20.6 µg/l	aquatic organisms	freshwater	short-term (single instance)
Zinc oxide	1314-13-2	PNEC	6.1 µg/l	aquatic organisms	marine water	short-term (single instance)
Zinc oxide	1314-13-2	PNEC	100 µg/l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
Zinc oxide	1314-13-2	PNEC	117.8 mg/kg	aquatic organisms	freshwater sediment	short-term (single instance)
Zinc oxide	1314-13-2	PNEC	56.5 mg/kg	aquatic organisms	marine sediment	short-term (single instance)
Zinc oxide	1314-13-2	PNEC	35.6 mg/kg	terrestrial organisms	soil	short-term (single instance)
Acetone	67-64-1	PNEC	10.6 mg/l	aquatic organisms	freshwater	short-term (single instance)
Acetone	67-64-1	PNEC	1.06 mg/l	aquatic organisms	marine water	short-term (single instance)
Acetone	67-64-1	PNEC	100 mg/l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
Acetone	67-64-1	PNEC	30.4 mg/kg	aquatic organisms	freshwater sediment	short-term (single instance)
Acetone	67-64-1	PNEC	3.04 mg/kg	aquatic organisms	marine sediment	short-term (single instance)
Acetone	67-64-1	PNEC	29.5 mg/kg	terrestrial organisms	soil	short-term (single instance)
Fatty acids, tall-oil, reaction products with diethylenetriamine	61790-69-0	PNEC	10 µg/l	aquatic organisms	freshwater	short-term (single instance)
Fatty acids, tall-oil, reaction products with diethylenetriamine	61790-69-0	PNEC	1 µg/l	aquatic organisms	marine water	short-term (single instance)

Zinc-Spray 700 Klostermann Chemie

Version number: GHS 2.1
Replaces version of: 19.04.2021 (GHS 1)

Revision: 25.11.2021

Relevant PNECs of components of the mixture						
Name of substance	CAS No	Endpoint	Threshold level	Organism	Environmental compartment	Exposure time
Fatty acids, tall-oil, reaction products with diethylenetriamine	61790-69-0	PNEC	100 mg/l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
Fatty acids, tall-oil, reaction products with diethylenetriamine	61790-69-0	PNEC	900,000 mg/kg	aquatic organisms	freshwater sediment	short-term (single instance)
Fatty acids, tall-oil, reaction products with diethylenetriamine	61790-69-0	PNEC	90,000 mg/kg	aquatic organisms	marine sediment	short-term (single instance)
Fatty acids, tall-oil, reaction products with diethylenetriamine	61790-69-0	PNEC	1,080,000 mg/kg	terrestrial organisms	soil	short-term (single instance)

8.2 Exposure controls

Appropriate engineering controls
General ventilation.

Individual protection measures (personal protective equipment)



Eye/face protection

Use protective eyewear to guard against splash of liquids.

Skin protection

- Hand protection

Wear protective gloves.

- Other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended. Wash hands thoroughly after handling.

Respiratory protection

During spraying wear suitable respiratory equipment.

Environmental exposure controls

Use appropriate container to avoid environmental contamination. Keep away from drains, surface and ground water.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state	liquid, solid, gaseous (spray aerosol)
Colour	dark grey
Odour	characteristic
Melting point/freezing point	-187.6 °C at 1,013 hPa
Boiling point or initial boiling point and boiling range	not applicable (aerosol)
Flammability	flammable aerosol in accordance with GHS criteria

Zinc-Spray 700 Klostermann Chemie

Version number: GHS 2.1
Replaces version of: 19.04.2021 (GHS 1)

Revision: 25.11.2021

Lower and upper explosion limit	1.1 vol% - 15 vol%
Flash point	not applicable (aerosol)
Auto-ignition temperature	>400 °C (auto-ignition temperature (liquids and gases))
Decomposition temperature	not relevant
pH (value)	not applicable (aerosol)
Kinematic viscosity	not relevant
Solubility(ies)	not determined

Partition coefficient

Partition coefficient n-octanol/water (log value)	this information is not available
---	-----------------------------------

Vapour pressure	4,200 hPa at 20 °C
-----------------	--------------------

Density and/or relative density

Density	0.8409 – 0.8535 g/ml
Relative vapour density	information on this property is not available

Particle characteristics	not relevant (aerosol)
--------------------------	------------------------

9.2 Other information

Information with regard to physical hazard classes

Aerosols

- Components (flammable)	68.1 %
--------------------------	--------

Other safety characteristics

Temperature class (EU, acc. to ATEX)	T2 (maximum permissible surface temperature on the equipment: 300°C)
--------------------------------------	--

SECTION 10: Stability and reactivity

10.1 Reactivity

Concerning incompatibility: see below "Conditions to avoid" and "Incompatible materials". The mixture contains reactive substance(s). Risk of ignition.

10.2 Chemical stability

See below "Conditions to avoid".

10.3 Possibility of hazardous reactions

No known hazardous reactions.

Zinc-Spray 700 Klostermann Chemie

Version number: GHS 2.1
Replaces version of: 19.04.2021 (GHS 1)

Revision: 25.11.2021

10.4 Conditions to avoid

Do not spray on an open flame or other ignition source. Keep away from heat.

Hints to prevent fire or explosion

Protect from sunlight.

10.5 Incompatible materials

Oxidisers

10.6 Hazardous decomposition products

Reasonably anticipated hazardous decomposition products produced as a result of use, storage, spill and heating are not known. Hazardous combustion products: see section 5.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Test data are not available for the complete mixture.

Classification procedure

The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

Classification according to GHS (1272/2008/EC, CLP)

Acute toxicity

Shall not be classified as acutely toxic.

Acute toxicity estimate (ATE) of components of the mixture			
Name of substance	CAS No	Exposure route	ATE
Xylene	1330-20-7	dermal	1,100 mg/kg
Xylene	1330-20-7	inhalation: vapour	11 mg/l/4h
Ethylbenzene	100-41-4	inhalation: vapour	11 mg/l/4h
Fatty acids, tall-oil, reaction products with diethylenetriamine	61790-69-0	oral	500 mg/kg

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/eye irritation

Shall not be classified as seriously damaging to the eye or eye irritant.

Respiratory or skin sensitisation

Shall not be classified as a respiratory or skin sensitiser.

Germ cell mutagenicity

Shall not be classified as germ cell mutagenic.

Carcinogenicity

Shall not be classified as carcinogenic.

Reproductive toxicity

Shall not be classified as a reproductive toxicant.

Specific target organ toxicity - single exposure

Shall not be classified as a specific target organ toxicant (single exposure).

Specific target organ toxicity - repeated exposure

Shall not be classified as a specific target organ toxicant (repeated exposure).

Zinc-Spray 700 Klostermann Chemie

Version number: GHS 2.1
Replaces version of: 19.04.2021 (GHS 1)

Revision: 25.11.2021

Aspiration hazard

Shall not be classified as presenting an aspiration hazard.

11.2 Information on other hazards

There is no additional information.

SECTION 12: Ecological information

12.1 Toxicity

Acc. to 1272/2008/EC: Very toxic to aquatic life with long lasting effects.
Verordnung über Anlagen zum Umgang mit wassergefährdenden Stoffen (Ordinance on facilities for handling substances hazardous to water) (AwSV): WGK 2, obviously hazardous to water (Germany)

12.2 Persistence and degradability

Degradability of components of the mixture

Name of substance	CAS No	Process	Degradation rate	Time	Method	Source
Xylene	1330-20-7	oxygen depletion	98 %	28 d		ECHA
Acetone	67-64-1	carbon dioxide generation	90.9 %	28 d		ECHA
Hydrocarbons, C9, aromatics	64742-95-6	oxygen depletion	30.9 %	2 d		ECHA
Fatty acids, tall-oil, reaction products with diethylenetriamine	61790-69-0	oxygen depletion	24 %	28 d		ECHA
Fatty acids, tall-oil, reaction products with diethylenetriamine	61790-69-0	carbon dioxide generation	31 %	28 d		ECHA

12.3 Bioaccumulative potential

Data are not available.

Bioaccumulative potential of components of the mixture

Name of substance	CAS No	BCF	Log KOW	BOD5/COD
Butane	106-97-8		1.09 (pH value: 7, 20 °C)	
Propane	74-98-6		2.8 (pH value: 7, 20 °C)	
Xylene	1330-20-7	>5.5 – <12.2	3.2 (pH value: 7, 20 °C)	
Ethylbenzene	100-41-4	1	3.6 (pH value: 7.84, 20 °C)	
Zinc oxide	1314-13-2	0.002		
Acetone	67-64-1		-0.23	963.5
Fatty acids, tall-oil, reaction products with diethylenetriamine	61790-69-0	7.76	6 (20 °C)	

12.4 Mobility in soil

Data are not available.

12.5 Results of PBT and vPvB assessment

Data are not available.

Zinc-Spray 700 Klostermann Chemie

Version number: GHS 2.1
Replaces version of: 19.04.2021 (GHS 1)

Revision: 25.11.2021

12.6 Endocrine disrupting properties

Information on this property is not available.

12.7 Other adverse effects

Data are not available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Sewage disposal-relevant information

Do not empty into drains. Avoid release to the environment. Refer to special instructions/safety data sheets.

Waste treatment of containers/packagings

It is a dangerous waste; only packagings which are approved (e.g. acc. to ADR) may be used. Completely emptied packages can be recycled. Handle contaminated packages in the same way as the substance itself.

Remarks

Please consider the relevant national or regional provisions. Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities.

SECTION 14: Transport information

14.1 UN number or ID number

ADR/RID/ADN	UN 1950
IMDG-Code	UN 1950
ICAO-TI	UN 1950

14.2 UN proper shipping name

ADR/RID/ADN	AEROSOLS
IMDG-Code	AEROSOLS
ICAO-TI	Aerosols, flammable

14.3 Transport hazard class(es)

ADR/RID/ADN	2 (2.1)
IMDG-Code	2.1
ICAO-TI	2.1

14.4 Packing group

not assigned

14.5 Environmental hazards

hazardous to the aquatic environment

14.6 Special precautions for user

There is no additional information.

14.7 Maritime transport in bulk according to IMO instruments

The cargo is not intended to be carried in bulk.

Information for each of the UN Model Regulations

Zinc-Spray 700 Klostermann Chemie

Version number: GHS 2.1
Replaces version of: 19.04.2021 (GHS 1)

Revision: 25.11.2021

Transport of dangerous goods by road, rail and inland waterway (ADR/RID/ADN) - Additional information

Classification code 5F
Danger label(s) 2.1, fish and tree



Environmental hazards YES (hazardous to the aquatic environment)
Special provisions (SP) 190, 327, 344, 625
Excepted quantities (EQ) E0
Limited quantities (LQ) 1 L
Transport category (TC) 2
Tunnel restriction code (TRC) D

International Maritime Dangerous Goods Code (IMDG) - Additional information

Marine pollutant YES (hazardous to the aquatic environment) (Zinc powder - zinc dust (stabilized))
Danger label(s) 2.1, fish and tree



Special provisions (SP) 63, 190, 277, 327, 344, 381, 959
Excepted quantities (EQ) E0
Limited quantities (LQ) 1 L
EmS F-D, S-U
Stowage category -

International Civil Aviation Organization (ICAO-IATA/DGR) - Additional information

Environmental hazards YES (hazardous to the aquatic environment)
Danger label(s) 2.1



Special provisions (SP) A145, A167
Excepted quantities (EQ) E0
Limited quantities (LQ) 30 kg

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Relevant provisions of the European Union (EU)

Deco-Paint Directive (2004/42/EC)

VOC content	69.68 % 594.7 g/l
-------------	----------------------

National regulations (Germany)

Zinc-Spray 700 Klostermann Chemie

Version number: GHS 2.1
Replaces version of: 19.04.2021 (GHS 1)

Revision: 25.11.2021

Verordnung über Anlagen zum Umgang mit wassergefährdenden Stoffen (Ordinance on facilities for handling substances hazardous to water) (AwSV)

Wassergefährdungsklasse, WGK 2 obviously hazardous to water
(water hazard class)

Technical instructions on air quality control (Germany)

Number	Group of substances	Class	Conc.	Mass flow	Mass concentration	Notation
5.2.5	organic substances		≥ 25 wt%	0.5 kg/h	50 mg/m ³	3)

Notation

3) a total mass flow of 0.50 kg/h or a total mass concentration of 50 mg/m³, each of which to be indicated as total carbon, shall not be exceeded (except organic particulate matter)

Storage of hazardous substances in non-stationary containers (TRGS 510) (Germany)

Storage class (LGK) 2 B (aerosol dispensers and lighters)

15.2 Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Indication of changes (revised safety data sheet)

Section	Former entry (text/value)	Actual entry (text/value)	Safety-relevant
1.1		Unique formula identifier (UFI): 2A20-U0DS-100W-PM43	yes
8.1		Biological limit values: change in the listing (table)	yes
14.6	Special precautions for user: Provisions for dangerous goods (ADR) should be complied within the premises.	Special precautions for user: There is no additional information.	yes
15.1		Technical instructions on air quality control (Germany)	yes
15.1		Technical instructions on air quality control (Germany): change in the listing (table)	yes
16		Abbreviations and acronyms: change in the listing (table)	yes

Abbreviations and acronyms

Abbr.	Descriptions of used abbreviations.
2000/39/EC.	Commission Directive establishing a first list of indicative occupational exposure limit values in implementation of Council Directive 98/24/EC.
Acute Tox.	Acute toxicity.
ADN.	Accord européen relatif au transport international des marchandises dangereuses par voies de navigation intérieures (European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways).
ADR.	Accord relatif au transport international des marchandises dangereuses par route (Agreement concerning the International Carriage of Dangerous Goods by Road).
ADR/RID/ADN.	Agreements concerning the International Carriage of Dangerous Goods by Road/Rail/Inland Waterways (ADR/RID/ADN).
AGW.	Workplace exposure limit.
Aquatic Acute.	Hazardous to the aquatic environment - acute hazard.
Aquatic Chronic.	Hazardous to the aquatic environment - chronic hazard.
Asp. Tox.	Aspiration hazard.
ATE.	Acute Toxicity Estimate.
BCF.	Bioconcentration factor.
BOD.	Biochemical Oxygen Demand.

Zinc-Spray 700 Klostermann Chemie

Version number: GHS 2.1
Replaces version of: 19.04.2021 (GHS 1)

Revision: 25.11.2021

Abbr.	Descriptions of used abbreviations.
CAS.	Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances).
Ceiling-C.	Ceiling value.
CLP.	Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures.
COD.	Chemical oxygen demand.
DFG.	Deutsche Forschungsgemeinschaft MAK-und BAT-Werte-Liste, Senatskommission zur Prüfung gesundheitsschädlicher Arbeitsstoffe, Wiley-VCH, Weinheim.
DGR.	Dangerous Goods Regulations (see IATA/DGR).
DNEL.	Derived No-Effect Level.
EC No.	The EC Inventory (EINECS, ELINCS and the NLP-list) is the source for the seven-digit EC number, an identifier of substances commercially available within the EU (European Union).
EINECS.	European Inventory of Existing Commercial Chemical Substances.
ELINCS.	European List of Notified Chemical Substances.
EmS.	Emergency Schedule.
Eye Dam.	Seriously damaging to the eye.
Eye Irrit.	Irritant to the eye.
Flam. Gas.	Flammable gas.
Flam. Liq.	Flammable liquid.
GHS.	"Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Nations.
IATA.	International Air Transport Association.
IATA/DGR.	Dangerous Goods Regulations (DGR) for the air transport (IATA).
ICAO.	International Civil Aviation Organization.
ICAO-TI.	Technical instructions for the safe transport of dangerous goods by air.
IMDG.	International Maritime Dangerous Goods Code.
IMDG-Code.	International Maritime Dangerous Goods Code.
Index No.	The Index number is the identification code given to the substance in Part 3 of Annex VI to Regulation (EC) No 1272/2008.
IOELV.	Indicative occupational exposure limit value.
LGK.	Lagerklasse (storage class according to TRGS 510, Germany).
Log KOW.	n-Octanol/water.
NLP.	No-Longer Polymer.
PBT.	Persistent, Bioaccumulative and Toxic.
PNEC.	Predicted No-Effect Concentration.
Ppm.	Parts per million.
Press. Gas.	Gas under pressure.
RCP.	Reciprocal calculation procedure.
REACH.	Registration, Evaluation, Authorisation and Restriction of Chemicals.
RID.	Règlement concernant le transport International ferroviaire des marchandises Dangereuses (Regulations concerning the International carriage of Dangerous goods by Rail).
Skin Corr.	Corrosive to skin.
Skin Irrit.	Irritant to skin.
Skin Sens.	Skin sensitisation.
STEL.	Short-term exposure limit.
STOT RE.	Specific target organ toxicity - repeated exposure.
STOT SE.	Specific target organ toxicity - single exposure.
TRGS.	Technische Regeln für Gefahrstoffe (technical rules for hazardous substances, Germany).
TRGS 900.	Arbeitsplatzgrenzwerte (TRGS 900).
TRGS 903.	Biologische Grenzwerte (TRGS 903).
TWA.	Time-weighted average.
VOC.	Volatile Organic Compounds.
VPvB.	Very Persistent and very Bioaccumulative.

Key literature references and sources for data

Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures. Regulation (EC) No. 1907/2006 (REACH), amended by 2020/878/EU.

Transport of dangerous goods by road, rail and inland waterway (ADR/RID/ADN). International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).

Classification procedure

Physical and chemical properties: The classification is based on tested mixture.

Health hazards, Environmental hazards: The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

List of relevant phrases (code and full text as stated in section 2 and 3)

Code.	Text.
H220.	Extremely flammable gas.
H222.	Extremely flammable aerosol.
H225.	Highly flammable liquid and vapour.
H226.	Flammable liquid and vapour.
H229.	Pressurised container: May burst if heated.
H280.	Contains gas under pressure; may explode if heated.
H302.	Harmful if swallowed.
H304.	May be fatal if swallowed and enters airways.
H312.	Harmful in contact with skin.
H314.	Causes severe skin burns and eye damage.
H315.	Causes skin irritation.
H317.	May cause an allergic skin reaction.

Zinc-Spray 700 Klostermann Chemie

Version number: GHS 2.1
Replaces version of: 19.04.2021 (GHS 1)

Revision: 25.11.2021

Code.	Text.
H319.	Causes serious eye irritation.
H332.	Harmful if inhaled.
H335.	May cause respiratory irritation.
H336.	May cause drowsiness or dizziness.
H373.	May cause damage to organs through prolonged or repeated exposure.
H400.	Very toxic to aquatic life.
H410.	Very toxic to aquatic life with long lasting effects.
H411.	Toxic to aquatic life with long lasting effects.
H412.	Harmful to aquatic life with long lasting effects.

Disclaimer

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.