

Anti-Seez-Spray Klostermann Chemie

Version number: GHS 2.1
Replaces version of: 19.07.2021 (GHS 1)

Revision: 25.11.2021

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name	Anti-Seez-Spray Klostermann Chemie
Unique formula identifier (UFI)	1G10-S0GS-Y00Y-269F

Article number	983
----------------	-----

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses	Lubricant Industrial uses Professional uses Consumer uses
--------------------------	--

1.3 Details of the supplier of the safety data sheet

Klostermann Chemie GmbH & Co.KG
Von-dem-Bussche-Münch-Straße 4
32339 Espelkamp
Germany

Telephone: +49 (0) 5772 6711
e-mail: info@klostermann-chemie.de
Website: www.klostermann-chemie.de

e-mail (competent person)	info@klostermann-chemie.de (Tim Schürstedt)
---------------------------	---

1.4 Emergency telephone number

Poison centre		
Name	Postal code/city	Telephone
Beratungsstelle bei Vergiftungen Giftinformationszentrale der Länder Rheinland-Pfalz und Hessen	55131 Mainz	+49 (0) 6131-19240

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 (CLP)

Section	Hazard class	Category	Hazard class and category	Hazard statement
2.3	aerosols	1	Aerosol 1	H222,H229
3.2	skin corrosion/irritation	2	Skin Irrit. 2	H315
3.3	serious eye damage/eye irritation	2	Eye Irrit. 2	H319
3.8D	specific target organ toxicity - single exposure (narcotic effects, drowsiness)	3	STOT SE 3	H336
4.1C	hazardous to the aquatic environment - chronic hazard	3	Aquatic Chronic 3	H412

For full text of abbreviations: see SECTION 16.

The most important adverse physicochemical, human health and environmental effects
Spillage and fire water can cause pollution of watercourses.

2.2 Label elements

Anti-Seez-Spray Klostermann Chemie

Version number: GHS 2.1
Replaces version of: 19.07.2021 (GHS 1)

Revision: 25.11.2021

Labelling according to Regulation (EC) No 1272/2008 (CLP)

- Signal word danger

- Pictograms

GHS02, GHS07



- Hazard statements

H222 Extremely flammable aerosol.
H229 Pressurised container: May burst if heated.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.
H412 Harmful to aquatic life with long lasting effects.

- Precautionary statements

P101 If medical advice is needed, have product container or label at hand.
P102 Keep out of reach of children.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211 Do not spray on an open flame or other ignition source.
P251 Do not pierce or burn, even after use.
P271 Use only outdoors or in a well-ventilated area.
P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

- Hazardous ingredients for labelling

Special petrol 60/95, Propan-2-ol

2.3 Other hazards

of no significance





SECTION 3: Composition/information on ingredients

3.1 Substances

Not relevant (mixture)

3.2 Mixtures








Description of the mixture

Name of substance	Identifier	Wt%	Classification acc. to GHS	Pictograms
Butane	CAS No 106-97-8 EC No 203-448-7 REACH Reg. No 01-2119474691-32- xxxx	25 – < 50	Flam. Gas 1A / H220 Press. Gas L / H280	 
Propane	CAS No 74-98-6 EC No 200-827-9 REACH Reg. No 01-2119486944-21- xxxx	10 – < 25	Flam. Gas 1A / H220 Press. Gas L / H280	 

Anti-Seez-Spray Klostermann Chemie

Version number: GHS 2.1
Replaces version of: 19.07.2021 (GHS 1)

Revision: 25.11.2021

Name of substance	Identifier	Wt%	Classification acc. to GHS	Pictograms
Special petrol 60/95	CAS No 92128-66-0 EC No 921-024-6 Index No 649-328-00-1 REACH Reg. No 01-2119475514-35- xxxx	10 – < 25	Flam. Liq. 2 / H225 Skin Irrit. 2 / H315 STOT SE 3 / H336 Asp. Tox. 1 / H304 Aquatic Chronic 2 / H411	   
Propan-2-ol	CAS No 67-63-0 EC No 200-661-7 REACH Reg. No 01-2119457558-25- xxxx	1 – < 5	Flam. Liq. 2 / H225 Eye Irrit. 2 / H319 STOT SE 3 / H336	 
Aluminum powder (stabilized)	CAS No 7429-90-5 EC No 231-072-3	1 – < 5	Flam. Sol. 1 / H228	

For full text of abbreviations: see SECTION 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General notes

Do not leave affected person unattended. Remove victim out of the danger area. Keep affected person warm, still and covered. Take off immediately all contaminated clothing. In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness place person in the recovery position. Never give anything by mouth.

Following inhalation

If breathing is irregular or stopped, immediately seek medical assistance and start first aid actions. In case of respiratory tract irritation, consult a physician. Provide fresh air.

Following skin contact

Wash with plenty of soap and water.

Following eye contact

Remove contact lenses, if present and easy to do. Continue rinsing. Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart.

Following ingestion

Rinse mouth with water (only if the person is conscious). Do NOT induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed

Narcotic effects.

4.3 Indication of any immediate medical attention and special treatment needed

none

Anti-Seez-Spray Klostermann Chemie

Version number: GHS 2.1
Replaces version of: 19.07.2021 (GHS 1)

Revision: 25.11.2021

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Water spray, BC-powder

Unsuitable extinguishing media

Water jet

5.2 Special hazards arising from the substance or mixture

Hazardous combustion products

Carbon monoxide (CO), Carbon dioxide (CO₂)

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Co-ordinate firefighting measures to the fire surroundings. Do not allow firefighting water to enter drains or water courses. Collect contaminated firefighting water separately. Fight fire with normal precautions from a reasonable distance.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Remove persons to safety.

For emergency responders

Wear breathing apparatus if exposed to vapours/dust/spray/gases.

6.2 Environmental precautions

Keep away from drains, surface and ground water. Retain contaminated washing water and dispose of it.

6.3 Methods and material for containment and cleaning up

Advice on how to contain a spill

Covering of drains

Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.

6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Recommendations

- Measures to prevent fire as well as aerosol and dust generation

Use local and general ventilation. Use only in well-ventilated areas.

Advice on general occupational hygiene

Wash hands after use. Do not eat, drink and smoke in work areas. Remove contaminated clothing and protective equipment before entering eating areas. Never keep food or drink in the vicinity of chemicals. Never place chemicals in containers that are normally used for food or drink. Keep away from food, drink and animal feedingstuffs.

7.2 Conditions for safe storage, including any incompatibilities

Managing of associated risks

- Flammability hazards

Do not spray on an open flame or other ignition source. Protect from sunlight.

Anti-Seez-Spray Klostermann Chemie

Version number: GHS 2.1
Replaces version of: 19.07.2021 (GHS 1)

Revision: 25.11.2021

- Packaging compatibilities
- Keep only in original container.

7.3 Specific end use(s)

See section 16 for a general overview.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limit values (Workplace Exposure Limits)											
Country	Name of agent	CAS No	Identifier	TWA [ppm]	TWA [mg/m ³]	STEL [ppm]	STEL [mg/m ³]	Ceiling-C [ppm]	Ceiling-C [mg/m ³]	Notation	Source
DE	butane	106-97-8	AGW	1,000	2,400	4,000	9,600				TRGS 900
DE	n-butane	106-97-8	MAK	1,000	2,400	4,000	9,600				DFG
DE	2-propanol	67-63-0	MAK	200	500	400	1,000				DFG
DE	propan-2-ol	67-63-0	AGW	200	500	400	1,000			Y	TRGS 900
DE	propane	74-98-6	AGW	1,000	1,800	4,000	7,200				TRGS 900
DE	propane	74-98-6	MAK	1,000	1,800	4,000	7,200				DFG
DE	aluminium	7429-90-5	MAK		1.5					r	DFG
DE	aluminium	7429-90-5	MAK		4					dust, i	DFG

Notation

Ceiling-C

dust

i

r

STEL

TWA

Y

ceiling value is a limit value above which exposure should not occur

as dust

inhalable fraction

respirable fraction

short-term exposure limit: a limit value above which exposure should not occur and which is related to a 15-minute period (unless otherwise specified)

time-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8 hours

time-weighted average (unless otherwise specified)

a risk of developmental toxicity does not need to be expected if the occupational exposure limit value and the biological limit value (BGW) are adhered to

Biological limit values						
Country	Name of agent	Parameter	Notation	Identifier	Value	Source
DE	2-propanol	acetone		BAT	25 mg/l	DFG
DE	2-propanol	acetone		BAT	25 mg/l	DFG
DE	2-propanol	acetone		BLV	25 mg/l	TRGS 903
DE	2-propanol	acetone		BLV	25 mg/l	TRGS 903
DE	aluminium	aluminium	crea	BAT	50 µg/g	DFG
DE	aluminium	aluminium	crea	BAT (BAR)	15 µg/g	DFG
DE	aluminium	aluminium	crea	BLV	50 µg/l	TRGS 903

Notation

crea

creatinine

Anti-Seez-Spray Klostermann Chemie

Version number: GHS 2.1
Replaces version of: 19.07.2021 (GHS 1)

Revision: 25.11.2021

Relevant DNELs of components of the mixture						
Name of substance	CAS No	Endpoint	Threshold level	Protection goal, route of exposure	Used in	Exposure time
Special petrol 60/95	92128-66-0	DNEL	2,035 mg/m ³	human, inhalatory	worker (industry)	chronic - systemic effects
Special petrol 60/95	92128-66-0	DNEL	773 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects
Propan-2-ol	67-63-0	DNEL	500 mg/m ³	human, inhalatory	worker (industry)	chronic - systemic effects
Propan-2-ol	67-63-0	DNEL	888 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects

Relevant PNECs of components of the mixture						
Name of substance	CAS No	Endpoint	Threshold level	Organism	Environmental compartment	Exposure time
Propan-2-ol	67-63-0	PNEC	140.9 mg/l	aquatic organisms	freshwater	short-term (single instance)
Propan-2-ol	67-63-0	PNEC	140.9 mg/l	aquatic organisms	marine water	short-term (single instance)
Propan-2-ol	67-63-0	PNEC	2,251 mg/l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
Propan-2-ol	67-63-0	PNEC	552 mg/kg	aquatic organisms	freshwater sediment	short-term (single instance)
Propan-2-ol	67-63-0	PNEC	552 mg/kg	aquatic organisms	marine sediment	short-term (single instance)
Propan-2-ol	67-63-0	PNEC	28 mg/kg	terrestrial organisms	soil	short-term (single instance)

8.2 Exposure controls

Appropriate engineering controls

General ventilation.

Individual protection measures (personal protective equipment)



Eye/face protection

Use protective eyewear to guard against splash of liquids.

Skin protection

- Hand protection

Wear protective gloves.

- Other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended. Wash hands thoroughly after handling.

Respiratory protection

During spraying wear suitable respiratory equipment.

Environmental exposure controls

Use appropriate container to avoid environmental contamination. Keep away from drains, surface and ground water.

Anti-Seez-Spray Klostermann Chemie

Version number: GHS 2.1
Replaces version of: 19.07.2021 (GHS 1)

Revision: 25.11.2021

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state	liquid, solid, gaseous (spray aerosol)
Colour	white - light grey
Odour	characteristic
Melting point/freezing point	not determined
Boiling point or initial boiling point and boiling range	not applicable (aerosol)
Flammability	flammable aerosol in accordance with GHS criteria
Lower and upper explosion limit	30 g/m ³ / 5 vol% - 15 vol%
Flash point	not applicable (aerosol)
Auto-ignition temperature	>200 °C (auto-ignition temperature (liquids and gases))
Decomposition temperature	not relevant
pH (value)	not applicable (aerosol)
Kinematic viscosity	not relevant
Solubility(ies)	not determined

Partition coefficient

Partition coefficient n-octanol/water (log value)	this information is not available
---	-----------------------------------

Vapour pressure	4,200 hPa at 20 °C
-----------------	--------------------

Density and/or relative density

Density	0.7165 – 0.7256 g/ml
Relative vapour density	information on this property is not available

Particle characteristics	not relevant (aerosol)
--------------------------	------------------------

9.2 Other information

Information with regard to physical hazard classes

Aerosols

- Components (flammable)	64.84 %
--------------------------	---------

Anti-Seez-Spray Klostermann Chemie

Version number: GHS 2.1
Replaces version of: 19.07.2021 (GHS 1)

Revision: 25.11.2021

Other safety characteristics

Temperature class (EU, acc. to ATEX)	T3 (maximum permissible surface temperature on the equipment: 200°C)
--------------------------------------	--

SECTION 10: Stability and reactivity

10.1 Reactivity

Concerning incompatibility: see below "Conditions to avoid" and "Incompatible materials". The mixture contains reactive substance(s). Risk of ignition.

10.2 Chemical stability

See below "Conditions to avoid".

10.3 Possibility of hazardous reactions

No known hazardous reactions.

10.4 Conditions to avoid

Do not spray on an open flame or other ignition source. Keep away from heat.

Hints to prevent fire or explosion

Protect from sunlight.

10.5 Incompatible materials

Oxidisers

10.6 Hazardous decomposition products

Reasonably anticipated hazardous decomposition products produced as a result of use, storage, spill and heating are not known. Hazardous combustion products: see section 5.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Test data are not available for the complete mixture.

Classification procedure

The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

Classification according to GHS (1272/2008/EC, CLP)

Acute toxicity

Shall not be classified as acutely toxic.

GHS of the United Nations, annex 4: May be harmful in contact with skin or if inhaled.

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/eye irritation

Causes serious eye irritation.

Respiratory or skin sensitisation

Shall not be classified as a respiratory or skin sensitiser.

Germ cell mutagenicity

Shall not be classified as germ cell mutagenic.

Carcinogenicity

Shall not be classified as carcinogenic.

Reproductive toxicity

Shall not be classified as a reproductive toxicant.

Anti-Seez-Spray Klostermann Chemie

Version number: GHS 2.1
Replaces version of: 19.07.2021 (GHS 1)

Revision: 25.11.2021

Specific target organ toxicity - single exposure

May cause drowsiness or dizziness.

Specific target organ toxicity - repeated exposure

Shall not be classified as a specific target organ toxicant (repeated exposure).

Aspiration hazard

Shall not be classified as presenting an aspiration hazard.

11.2 Information on other hazards

There is no additional information.

SECTION 12: Ecological information

12.1 Toxicity

Acc. to 1272/2008/EC: Harmful to aquatic life with long lasting effects.
Verordnung über Anlagen zum Umgang mit wassergefährdenden Stoffen (Ordinance on facilities for handling substances hazardous to water) (AwSV): WGK 3, highly hazardous to water (Germany)

12.2 Persistence and degradability

Degradability of components of the mixture						
Name of substance	CAS No	Process	Degradation rate	Time	Method	Source
Special petrol 60/95	92128-66-0	oxygen depletion	83 %	16 d		ECHA
Propan-2-ol	67-63-0	oxygen depletion	53 %	5 d		ECHA

12.3 Bioaccumulative potential

Data are not available.

Bioaccumulative potential of components of the mixture				
Name of substance	CAS No	BCF	Log KOW	BOD5/COD
Butane	106-97-8		1.09 (pH value: 7, 20 °C)	
Propane	74-98-6		2.8 (pH value: 7, 20 °C)	

12.4 Mobility in soil

Data are not available.

12.5 Results of PBT and vPvB assessment

Data are not available.

12.6 Endocrine disrupting properties

Information on this property is not available.

12.7 Other adverse effects

Data are not available.

Anti-Seez-Spray Klostermann Chemie

Version number: GHS 2.1
Replaces version of: 19.07.2021 (GHS 1)

Revision: 25.11.2021

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Sewage disposal-relevant information

Do not empty into drains. Avoid release to the environment. Refer to special instructions/safety data sheets.

Waste treatment of containers/packages

It is a dangerous waste; only packagings which are approved (e.g. acc. to ADR) may be used. Completely emptied packages can be recycled. Handle contaminated packages in the same way as the substance itself.

Remarks

Please consider the relevant national or regional provisions. Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities.

SECTION 14: Transport information

14.1 UN number or ID number

ADR/RID/ADN	UN 1950
IMDG-Code	UN 1950
ICAO-TI	UN 1950

14.2 UN proper shipping name

ADR/RID/ADN	AEROSOLS
IMDG-Code	AEROSOLS
ICAO-TI	Aerosols, flammable

14.3 Transport hazard class(es)

ADR/RID/ADN	2 (2.1)
IMDG-Code	2.1
ICAO-TI	2.1

14.4 Packing group

not assigned

14.5 Environmental hazards

non-environmentally hazardous acc. to the dangerous goods regulations

14.6 Special precautions for user

There is no additional information.

14.7 Maritime transport in bulk according to IMO instruments

The cargo is not intended to be carried in bulk.

Information for each of the UN Model Regulations

Transport of dangerous goods by road, rail and inland waterway (ADR/RID/ADN) - Additional information

Classification code	5F
Danger label(s)	2.1



Special provisions (SP)	190, 327, 344, 625
Excepted quantities (EQ)	E0
Limited quantities (LQ)	1 L

Anti-Seez-Spray Klostermann Chemie

Version number: GHS 2.1
Replaces version of: 19.07.2021 (GHS 1)

Revision: 25.11.2021

Transport category (TC)	2
Tunnel restriction code (TRC)	D
International Maritime Dangerous Goods Code (IMDG) - Additional information	
Marine pollutant	-
Danger label(s)	2.1



Special provisions (SP)	63, 190, 277, 327, 344, 381, 959
Excepted quantities (EQ)	E0
Limited quantities (LQ)	1 L
EmS	F-D, S-U
Stowage category	-
International Civil Aviation Organization (ICAO-IATA/DGR) - Additional information	
Danger label(s)	2.1



Special provisions (SP)	A145, A167
Excepted quantities (EQ)	E0
Limited quantities (LQ)	30 kg

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations (Germany)

Verordnung über Anlagen zum Umgang mit wassergefährdenden Stoffen (Ordinance on facilities for handling substances hazardous to water) (AwSV)

Wassergefährdungsklasse, WGK 3 highly hazardous to water
(water hazard class)

Technical instructions on air quality control (Germany)

Number	Group of substances	Class	Conc.	Mass flow	Mass concentration	Notation
5.2.5	organic substances		≥ 25 wt%	0.5 kg/h	50 mg/m ³	3)

Notation

3) a total mass flow of 0.50 kg/h or a total mass concentration of 50 mg/m³, each of which to be indicated as total carbon, shall not be exceeded (except organic particulate matter)

Storage of hazardous substances in non-stationary containers (TRGS 510) (Germany)

Storage class (LGK) 2 B (aerosol dispensers and lighters)

15.2 Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

Anti-Seez-Spray Klostermann Chemie

Version number: GHS 2.1
Replaces version of: 19.07.2021 (GHS 1)

Revision: 25.11.2021

SECTION 16: Other information

Indication of changes (revised safety data sheet)

Section	Former entry (text/value)	Actual entry (text/value)	Safety-relevant
2.1		Classification according to Regulation (EC) No 1272/2008 (CLP): change in the listing (table)	yes
2.2		- Hazard statements: change in the listing (table)	yes
9.1	Density: 0.6577 – 0.6654 g/ml	Density: 0.7165 – 0.7256 g/ml	yes
11.1	Acute toxicity: Shall not be classified as acutely toxic.	Acute toxicity: Shall not be classified as acutely toxic. GHS of the United Nations, annex 4: May be harmful in contact with skin or if inhaled.	yes
11.1	Serious eye damage/eye irritation: Shall not be classified as seriously damaging to the eye or eye irritant.	Serious eye damage/eye irritation: Causes serious eye irritation.	yes
12.1	Toxicity: Acc. to 1272/2008/EC: Harmful to aquatic life with long lasting effects. Verordnung über Anlagen zum Umgang mit wassergefährdenden Stoffen (Ordinance on facilities for handling substances hazardous to water) (AwSV): WGK 2, obviously hazardous to water (Germany)	Toxicity: Acc. to 1272/2008/EC: Harmful to aquatic life with long lasting effects. Verordnung über Anlagen zum Umgang mit wassergefährdenden Stoffen (Ordinance on facilities for handling substances hazardous to water) (AwSV): WGK 3, highly hazardous to water (Germany)	yes
15.1	Wassergefährdungsklasse, WGK (water hazard class): 2 obviously hazardous to water	Wassergefährdungsklasse, WGK (water hazard class): 3 highly hazardous to water	yes
16		Abbreviations and acronyms: change in the listing (table)	yes

Abbreviations and acronyms

Abbr.	Descriptions of used abbreviations.
ADN.	Accord européen relatif au transport international des marchandises dangereuses par voies de navigation intérieures (European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways).
ADR.	Accord relatif au transport international des marchandises dangereuses par route (Agreement concerning the International Carriage of Dangerous Goods by Road).
ADR/RID/ADN.	Agreements concerning the International Carriage of Dangerous Goods by Road/Rail/Inland Waterways (ADR/RID/ADN).
AGW.	Workplace exposure limit.
Aquatic Chronic.	Hazardous to the aquatic environment - chronic hazard.
Asp. Tox.	Aspiration hazard.
BCF.	Bioconcentration factor.
BOD.	Biochemical Oxygen Demand.
CAS.	Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances).
Ceiling-C.	Ceiling value.
CLP.	Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures.
COD.	Chemical oxygen demand.
DFG.	Deutsche Forschungsgemeinschaft MAK- und BAT-Werte-Liste, Senatskommission zur Prüfung gesundheitsschädlicher Arbeitsstoffe, Wiley-VCH, Weinheim.
DGR.	Dangerous Goods Regulations (see IATA/DGR).
DNEL.	Derived No-Effect Level.
EC No.	The EC Inventory (EINECS, ELINCS and the NLP-list) is the source for the seven-digit EC number, an identifier of substances commercially available within the EU (European Union).
EINECS.	European Inventory of Existing Commercial Chemical Substances.
ELINCS.	European List of Notified Chemical Substances.
EmS.	Emergency Schedule.
Eye Dam.	Seriously damaging to the eye.
Eye Irrit.	Irritant to the eye.
Flam. Gas.	Flammable gas.
Flam. Liq.	Flammable liquid.
Flam. Sol.	Flammable solid.
GHS.	"Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Nations.

Anti-Seez-Spray Klostermann Chemie

Version number: GHS 2.1
Replaces version of: 19.07.2021 (GHS 1)

Revision: 25.11.2021

Abbr.	Descriptions of used abbreviations.
IATA.	International Air Transport Association.
IATA/DGR.	Dangerous Goods Regulations (DGR) for the air transport (IATA).
ICAO.	International Civil Aviation Organization.
ICAO-TI.	Technical instructions for the safe transport of dangerous goods by air.
IMDG.	International Maritime Dangerous Goods Code.
IMDG-Code.	International Maritime Dangerous Goods Code.
Index No.	The Index number is the identification code given to the substance in Part 3 of Annex VI to Regulation (EC) No 1272/2008.
LGK.	Lagerklasse (storage class according to TRGS 510, Germany).
Log KOW.	n-Octanol/water.
NLP.	No-Longer Polymer.
PBT.	Persistent, Bioaccumulative and Toxic.
PNEC.	Predicted No-Effect Concentration.
Ppm.	Parts per million.
Press. Gas.	Gas under pressure.
REACH.	Registration, Evaluation, Authorisation and Restriction of Chemicals.
RID.	Règlement concernant le transport International ferroviaire des marchandises Dangereuses (Regulations concerning the International carriage of Dangerous goods by Rail).
Skin Corr.	Corrosive to skin.
Skin Irrit.	Irritant to skin.
STEL.	Short-term exposure limit.
STOT SE.	Specific target organ toxicity - single exposure.
TRGS.	Technische Regeln für Gefahrstoffe (technical rules for hazardous substances, Germany).
TRGS 900.	Arbeitsplatzgrenzwerte (TRGS 900).
TRGS 903.	Biologische Grenzwerte (TRGS 903).
TWA.	Time-weighted average.
VPvB.	Very Persistent and very Bioaccumulative.

Key literature references and sources for data

Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures. Regulation (EC) No. 1907/2006 (REACH), amended by 2020/878/EU.

Transport of dangerous goods by road, rail and inland waterway (ADR/RID/ADN). International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).

Classification procedure

Physical and chemical properties: The classification is based on tested mixture.

Health hazards, Environmental hazards: The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

List of relevant phrases (code and full text as stated in section 2 and 3)

Code.	Text.
H220.	Extremely flammable gas.
H222.	Extremely flammable aerosol.
H225.	Highly flammable liquid and vapour.
H228.	Flammable solid.
H229.	Pressurised container: May burst if heated.
H280.	Contains gas under pressure; may explode if heated.
H304.	May be fatal if swallowed and enters airways.
H315.	Causes skin irritation.
H319.	Causes serious eye irritation.
H336.	May cause drowsiness or dizziness.
H411.	Toxic to aquatic life with long lasting effects.
H412.	Harmful to aquatic life with long lasting effects.

Disclaimer

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.